

Technical Specification Sheet

Syncros - Smart Step LOOP

MODULAR TILE

Construction

Tufted, Multi-Level Loop

Tile Size

50 cm x 50 cm

Textile Yarn Type

ECONYL® Type 6 and Monofilament

Dye Method

Solution-Dyed

Nominal Tufted Face Weight

946 g/m²

Gauge

1/12

Stitches Per Centimeter

28.70

Tufts

2,100/100 cm²

Nominal Pile Height

6.48 mm

Nominal Total Thickness

9.9 mm

Nominal Total Weight

3,540 g/m²

Backing Type

PVC-Free WellBAC™ Comfort Cushion (Available with TractionBack®)

Recycled Content by Total Weight

33.3% Pre-Consumer
6.6% Post-Consumer

Flammability (Radiant Panel

ASTM-E-648)

≥0.45 (Class I)

Smoke Density (NPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70) or

ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134)

20% R.H., 21°C

≤3.5 KV, Permanent Conductive Fibre

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

Indoor Air Quality —

CRI Green Label Plus™

GLP.793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

12 Tiles per box (3m²)

