

Nuway Grid




Technical specifications

Nuway grid

	12mm Grid		17mm Grid	
	Rubber	Textile	Rubber	Textile
Maximum length per module	3000mm		3000mm	
Maximum width per module	750mm		750mm	
Maximum weight per module	23kg/m ²		23kg/m ²	
Depth to height of aluminium	12mm	12mm	17mm	17mm
Depth to height of infill	14mm	18mm	19mm	23mm
Infill material	Rubber	Burford/Coral Classic/ Coral Brush Activ	Rubber	Burford/Coral Classic/ Coral Brush Activ
Construction	Closed		Closed	
Total weight	10.5kg/m ²	Approx 9kg/m ²	17.2kg/m ²	Approx 15kg/m ²
Max static load	100kg/m ²		100kg/m ²	
Dynamic load 2 wheels 80mm, 20,000 passes	200kg		200kg	
Ramp frame model	ARF 50		ARF 70	
Manufacturing method	Entrance flooring system with carriers and rubber infills	Entrance flooring system with carriers and textile infills	Entrance flooring system with carriers and rubber infills	Entrance flooring system with carriers and textile infills
Wiper material	Rubber	Needlefelt/PVC backed textile	Rubber	Needlefelt/PVC backed textile
Pile material	N/A	100% Polyamide BCF	N/A	100% Polyamide BCF

Nuway grid 12mm




Nuway grid 12mm with rubber insert



Nuway grid 12mm with textile insert

Nuway grid 17mm



Nuway grid 17mm with rubber insert



Nuway grid 17mm with textile insert

Considerations

As with all aluminium matting systems of this type, in very brightly lit areas, the strong contrast between a light aluminium scraper bar and a dark wiper strip can sometimes create a strobe effect which should be avoided. To prevent disorientating pedestrians affected by this type of visual disturbance, consider using a less contrasting insert.

