

INTRAflex XT

Rollable 18mm Aluminium Entrance Matting



INTRAflex XT™




features

- Heavy Duty Recessed Aluminium Entrance Matting
- Suitable for internal & external applications
- A combination of rubber/brush/fibre inserts available for complete 'Zonal' system
- Optimum dirt & moisture removal
- Heel-proof Open or Closed Construction
- Fully rollable for ease of cleaning & maintenance
- Suitable for the highest traffic areas

100% recycled aluminium construction

profile



A 21mm

B 18mm

C 28mm Profile

D 33mm Module

1 Finished floor surface

2 Recessed matwell frame

3 Levelling latex to matwell base


4 Screed sub-floor

5 Screw fixings


specification

Product Reference	INTRAflex XT Heavy Duty Recessed Aluminium Entrance Matting
Installation	Into suitable recessed matwell area, with surface of the matting level with adjoining floor coverings Surface mounted applications with use of ramped edging
Location	High Traffic environments Internal Applications – Fibre, Brush and Ribbed Rubber Inserts External Applications – Brush and Ribbed Rubber Inserts
Construction	100% recycled aluminium. All inserts recyclable/re-usable Heel Proof Open Construction – allows dirt and moisture to fall through into the matwell below Closed Construction – Solid connecting strip preventing debris falling through into matwell
Weight	18kg/m ²
Depth	18mm
Temperature Resistance	Aluminium resistant -50°C to +90°C
Matwell Framing	INT021
Finish	Mill Finish aluminium as standard Anodised finish in any RAL colour available for special order

inserts



Polypropylene



Polyamide

